CERTOCLAV VACUUM PRO

THE LABORATORY STERILIZER WITH A REVOLUTIONARY USER INTERFACE





HIGHLY DEVELOPED FEATURES FOR COMFORTABLE USE



Mobility

- Mobile autoclave display can placed at your favorite position.
- Included mountable industrial stand ensures save stand.



Durability

- Mobile display with certified industrial grade.
- IP 64 protection and shock resistant.



High Performance

• Sterilisation of solid instruments within 20 minutes (Time including fractionated pre-vacuum and drying).



Innovation

- Connection of multiple autoclaves to local network.
- CertoCloud via Ethernet cable or wireless LAN.





ACCESSORY

Tablets

Art.-No.: CV-8-T-S-Pro CV-12-T-S-Pro CV-18-T-S-Pro

CV-18-T-S-Pro CV-22-T-S-Pro

Extra set of tablets for all models of CertoClav Class B sterilizers.



Art.-No.: CV-WD-3L CV-WD-5L

With a volume of 3 or 5 liters.



Sealing machine

Art.-No.: CV-SM-M CV-SM-L

2 sizes, incl. different types of packing strap.



CertoCloud

EASY DATA ACCESS AND STORAGE. ONLINE DEVICE MANAGEMENT.

- · Any kind of documentation according to the customers needs.
- Logging via USB-Stick, CF-Card, direct printer output or fully automatic to the CertoCloud.
- · Accessible via www.certocloud.com or as offline application.











Secure Connection

- SSL encryption
- Secure server
- 100 % data privacy



Multi Device Management

- Combine all devices in one account
- Create programs
- Disseminate programs to all devices



Long Term Data Storage

- All data stored for 10 years to fulfil documentation requirements
- Secure backup








CertoCloud

www.certocloud.com



Customization

- Custom reports
- Direct printing
- Freely definable data formats



Email Notifications

- Alarms
- Cycle complete
- Process data



User Management

- Individual accounts
- · Accounts linked to devices

CertoTouch

THE USER INTERFACE WITH ON-SCREEN TRAINING.



Step-by-Step video guides

- All usage steps explained
- No more need to train staff
- Videos can be skipped
- Ensures simple usage



Program Selection

- Detailed description
- Custom program

PROGRAMS	Vacuum Times	Sterilizing Time	Sterilizing Temperature	Sterilizing Pressure	Vacuum Persist Time	Dry Time
121°C SOLID	1	20 min	121°C	110 kPa		3 min
121° C POROUS	3	20 min	121°C	110 kPa		7 min
121° C HOLLOW	3	20 min	121°C	110 kPa		10 min
134° C SOLID	1	4 min	134° C	210 kPa		3 min
134° C POROUS	3	4 min	134° C	210 kPa		7 min
134° C HOLLOW	3	4 min	134° C	210 kPa		10 min
USER DEFINED	3	5 min	134° C	210 kPa		10 min
B-D TEST	3	3,5 min	134° C	210 kPa		7 min
VACUUM TEST				-80 kPa	15 min	
CLEAN PROCESS	3	5 min	105° C	20 kPa		10 min
PRIONEN	3	19 min	135° C	210 kPa		10 min





Protocol history

- Protocols stored locally
- Graphically displayed
- Errors explained detailed



Service

- Order spare parts On-Screen
- Message center
- CertoClav Academy videos



Advanced Multi-User Management

- Secure user management system that enable numerous members of personnel.
- Personal email and password, can also be used for CertoCloud account.
- User defined settings and accurate association of performed cycles with operators.



TECHNICAL DETAILS

	Vacuum Pro 8 L	Vacuum Pro 12L	Vacuum Pro 18L	Vacuum Pro 22 L				
Art. Nr.	CV-8-Vac-Pro	CV-12-Vac-Pro	CV-18-Vac-Pro	CV-22-Vac-Pro				
Description	Vacuum autoclave, Class B, GLP ready, Stand-alone							
Compliance	CE							
Rated Voltage, Output	220 V, 50 Hz, 2400 W							
Temperature Range	121° C - 134° C							
Max working pressure	0,23 MPA							
Chamber material	Stainless steel 304							
Interface	7 inch touch screen							
Safety	Electrical locker							
Equipment	Optional label printer, USB-Stick, Ethernet, Wireless LAN, CF-Card							
Product size	53,5 x 36,5 x 32 cm	53,5 x 36,5 x 32 cm	60 x 50 x 43 cm	60 x 50 x 43 cm				
Diameter	17 cm	20 cm	25 cm	25 cm				
Depth	32 cm	36 cm	35 cm	45 cm				
Volume	81	121	181	221				
Weight	52 kg	52 kg	65 kg	65 kg				
Languages	English, German							
CertoCloud Licence	Unlimited							
Warranty	2 years							



Certoclav Sterilizer GmbH Georg Grinninger-Str. 37 A-4050 Traun

Phone: +43 (0)7229 689 www.certoclav.com

 $\label{lem:continuous} \textbf{Orders, technical customer service, custom-manufacture, dealer verification:}$

Christina Bokesch, Phone: +43 (0)7229 689 26, Fax: +43 (0)7229 74 141

Email: bokesch@certoclav.com

Product Manager: Klaus David, Phone: +43 (0)7229 689 28, Email: david@certoclav.com Operating instructions, technical information and operation videos: www.certoclav.com.